

# SKR 115A-D - industry double contact relay, 3-pole



Industry double contact three pole relay in different versions.

## order numbers

serial version	SKR 115 A-D... VDC/AC
with mechanical position indication and manual actuation	

## contact specifications

contact material (Standard)	AgNi
contact material (Optional 1)	AgNi + 0.2 Micron Au
contact material (Optional 2)	AgNi + 0.5 Micron Au
contact type	double contact
nominal switching capacity	6 A 250 VAC 1 6 A 30 VDC 1
electric life expectancy at nominal load	≥100'000 operations
inrush current max.	30 A for 20 ms
switching current max	10 A
switching power range	0,3 VA(W) to 2500 VA
contact resistance	20 m Ohms

## options

electrical position indication	SKR 115 A-D-L...
with free wheel diode	SKR 115 A-D-F...
electrical position indication with free wheel diode	SKR 115 A-D-FL...
without manual actuation	SKR 115 A-D-B...
push-button actuation	SKR 115 A-D-T...
current coil	SKR 115 A-D-C...

(combinations with mechanical and electrical position indication and free-wheel diode are possible)

## general data

mechanic life expectancy	10 million AC, 20 million DC
mechanical switching frequency	20 Hz
pull-in time	12 ms at DC / 3-10 ms at AC
release time	3,5 ms at DC / 2-15 ms at AC
bounce time normally open contact	3,5 ms at DC / 3-6 ms at AC
bounce time normally closed contact	9 ms at DC / 6-11 ms at AC
shock resistance	AK: > 10 g
vibration resistance	10-55 Hz, AK: 10 g, RK: 3 g
test voltage, coil/contact	2500 V <sub>eff</sub>
test voltage, open contact	1500 V <sub>eff</sub>
test voltage, adjacent contact	2000 V <sub>eff</sub>
insulation resistance @ 500 VDC	200 M Ohms
weight	app. 80 g
installation situation	any
ambient temperature	max. +70 °C
protection standard	IP 40

## accessories

Plug in socket accessories (metal clamp)	ZKR 119 ZKR 008
Plug in socket accessories (metal clamp)	ZKE 118
accessories (timer module)	ZKR 008 STM 100

## tests, instructions

certificates	UL, CSA, VDE
insulation group	VDE 0110 / group C 250 VAC

